



Übersicht lieferbarer Extrudierter Stäbe;
Sonderformate auf Anfrage.

Schema of Extruded Rods;
special sizes on request.

∅ (mm)	Toleranz Tolerance (mm)	Gewicht Weight (kg/m)	Länge Length (mm)		
			1000	2000	3000
4	+0,3 -0	0,03	●	●	●
5	+0,3 -0	0,05	●	●	●
6	+0,4 -0	0,07	●	●	●
7	+0,4 -0	0,09	●	●	●
8	+0,4 -0	0,12	●	●	●
9	+0,4 -0	0,15	●	●	●
10	+0,4 -0	0,18	●	●	●
11	+0,8 -0	0,23	●	●	●
12	+0,8 -0	0,26	●	●	●
13	+0,8 -0	0,32	●	●	●
14	+0,8 -0	0,36	●	●	●
15	+0,8 -0	0,41	●	●	●
16	+0,8 -0	0,46	●	●	●
17	+0,8 -0	0,52	●	●	●
18	+0,8 -0	0,60	●	●	●
19	+0,8 -0	0,65	●	●	●
20	+0,8 -0	0,72	●	●	●
22	+1,2 -0	0,89	●	●	●
25	+1,2 -0	1,12	●	●	●
28	+1,2 -0	1,41	●	●	●
30	+1,2 -0	1,62	●	●	●
32	+1,6 -0	1,87	●	●	●
35	+1,6 -0	2,20	●	●	●
38	+1,6 -0	2,61	●	●	●
40	+1,6 -0	2,90	●	●	●
42	+2,0 -0	3,08	●	●	●
45	+2,0 -0	3,64	●	●	●
50	+2,0 -0	4,47	●	●	●
55	+2,4 -0	5,40	●	●	●
60	+2,4 -0	6,38	●	●	●
65	+2,8 -0	7,48	●	●	●
70	+2,8 -0	8,70	●	●	●
75	+3,2 -0	10,12	●	●	●
80	+3,2 -0	11,48	●	●	●
85	+3,6 -0	13,20	●	●	●
90	+3,6 -0	14,51	●	●	●
100	+4,0 -0	18,30	●	●	●
110	+5,0 -0	21,78	●	●	●
120	+5,0 -0	25,55	●	●	●
130	+5,0 -0	30,97	●		
140	+5,0 -0	36,06	●		
150	+5,0 -0	41,12	●		
160	+6,0 -0	46,65	●		

Geschliffene Stäbe sind ebenfalls lieferbar
Precision Ground rods also available

Genannte Gewichte dienen als Richtwerte
Weights stated are for guide purposes only

 Standardmaße Standard production
 Sondermaße Additional production

Längentoleranzen Tolerance on length: +2%

Extruded Rods Extrudierte Stäbe